

COMPOTECH SRL

	<p>Ball Valves Serie mini Cod. VII 2 or 3 ways threaded ends 1/8 NPT; 1/4NPT (std)</p> <ul style="list-style-type: none"> • Materials: PP ; PVC; Nylon; PVDF black • Seals: Buna-N; Ethyl. Prop.(EPDM); Viton • Operation: Max.Press.9 Bar; Max Temp.60 C° 		
	<p>BALL VALVE PP white 1/4 NPT fe. (Viton O-Ring)</p> <ul style="list-style-type: none"> • Max Press.: 9 Bar • Max.Temp.: 60 C° • Ball hole diam.: 7 mm <p>Sizes: H= 40mm L=45mm</p>	 <p>Dim. H= 40mm L=45mm</p>	<p>BALL VALVE PVDF black 1/4 NPT fe (Viton O-Ring)</p> <ul style="list-style-type: none"> • Max Press.: 9 Bar • Max.Temp.: 60 C° • Ball hole diam.: 7mm
<p>Cod VIIPP0104N04NB</p>		<p>VIIKY0104N04NN</p>	
	<p>BALL VALVE PVC gray Quick conn. type J-Guest tubing 1/ 4" or (6mm) OD Seals:Buna/EPDM/Viton Ball hole diam.: 7 mm</p>		<p>PLUG VALVE 90° PVC 1/4NPT fe *1/4 OD or 6mm Quick conn type J-Guest Seal: EPDM</p> <ul style="list-style-type: none"> *Max Press: 10 Bar *Max Temp: 70 C° * Ball hole diam.: 5mm <p>Cod VI4VC04N04RB</p>
<p>Size.: H= 40mm L=65mm</p>	<p>Cod VIIVC0104R04RG</p>		
	<p>3Ways Ball Valves (Inlet Center / Out left-right) PVC white or PP (option) * <u>Ends 1/4 NPT fem</u> *Seals: Viton or EPDM (option)</p> <ul style="list-style-type: none"> • Max. Press.: 9 Bar • Max.Temp.: 60 C° • Ball hole diam.: 7mm • Sizes: H= 60mm L=50mm 		
<p>VIIVC0304N04NB</p>		<p>Plastic band for fixing on Panel</p>	
	<p>3Ways Ball Valves (Inlet Center / Out left-right) PVC white or PP (option) * <u>Ends 1/4 NPT fem</u> *Seals: Viton or EPDM (option)</p> <ul style="list-style-type: none"> • Max. Press.: 9 Bar • Max.Temp.: 60 C° • Ball hole diam.: 7mm • Sizes: H= 60mm L=50mm 	<p>Other ends available on request</p>	
<p>VIIKY0304N04NV</p>			

COMPOTECH SRL

<p>Ball Valves Serie medium Cod. VI2 / VI3 2 or 3 ways threaded ends *1/4 *1/2 *3/4 NPT Fem</p> <ul style="list-style-type: none"> Materials: PP ; PVC; Nylon; PVDF black Seals: Buna-N; Ethyl. Prop.(EPDM); Viton Operation: Max.Press.9 Bar; Max Temp.60 C° 							
		<p>BALL VALVE PVC white Ends 1/4 NPT fe Seals EPDM (option Viton) *Max Press: 9 Bar *Max Temp.:60 C° L= 60mm D= 25mm Ball hole diam.: 11mm</p>				<p>BALL VALVE PP white Ends 1/2 NPT fe Seals Viton *Max Press: 9 Bar *Max Temp.:60 C° Ball hole diam.: 11mm L=85 mm Ex.:27 mm Body Diam: 26mm</p>	
<p>Cod VI2VC0104N04N</p>		<p>Cod VI2PP0108N08NV</p>					
		<p>BALL VALVE PVC gray Ends 3/4 NPT male x fem</p> <p>Seals <u>Buna(std)</u> *Max Press: 9 Bar *Max Temp.:60 C° Ball hole diam.: 12mm</p> <p>L: 60 mm Ex: 32 mm Cod VI3VC0112N12NM</p>				<p>BALL VALVE PVC gray Ends 1/2 NPT male x fem</p> <p>Seals <u>EPDM(std)</u> *Max Press: 9 Bar *Max Temp.:60 C° Ball hole diam.: 11mm</p> <p>L: 60 mm Diam: 30 mm Cod VI3VC0108N08NM</p>	
		<p>2 Ways Ball Valve black PVDF Ends: 1/2 NPT Fem.</p> <ul style="list-style-type: none"> Max.Press.: 9 Bar Max.Temp.: 60 C° Ball through hole: <u>11mm</u> Viton seals <p>Sizes: Ex. 27mm L= 85mm</p>				<p>3Ways Ball Valves (Inlet Center / Out left-right) PP white * <u>Ends 1/2 NPT fem</u> *Seals: EPDM (Viton option)</p> <ul style="list-style-type: none"> Max. Press.: 9 Bar Max.Temp.: 60 C° Ball hole diam.: 11 mm L= 70mm H=80mm 	
<p>VI2KY0108N08NV</p>		<p>Cod VI3PP0308N08NB</p>					
		<p>NEEDLE VALVE Polyprop. 1/4NPT Fem ends *Stem seal PTFE *Fine regulation cone 2,5° *Operation: Press:9 Bar Temp:60 C° Min flow dia.:4,5 mm Sizes H= 67mm L=50mm Nut for Panel mount (hole 22mm)</p>				<p>NEEDLE VALVE PVDF(Kynar) 1/4NPT Fem ends *Stem seal PTFE *Fine regulation cone 2,5° *Operation: Press.9 Bar Temp:60 C° Min flow dia.:4,5 mm Sizes H= 67mm L=50mm Nut for Panel mount (hole 22mm)</p>	
<p>VR1PP0104N04NB</p>		<p>VR1KY0104G0</p>					